

DECLARATION OF PERFORMANCE

CE/P6/001

Unique identification code of the product type:

Profile 6 and Farmscape fibre cement profiled sheets and fittings, NT.

Intended use: **Roofing and internal/external wall covering.**

Manufacturer: **Etex Exteriors Ltd, Wellington Road, Burton on Trent, DE14 2AP**

www. eternit.co.uk

System of assessment and verification of constancy of performance:: **System 3.**

Notified testing laboratory No 0833 performed the Reaction to Fire tests, Report No 151962

Declared performances:


Essential Characteristic	Performance	Harmonised Technical Specification
Mechanical resistance	C1X	EN494:2012+A1:2015
Impact resistance	Pass at 1380mm span	
External fire performance	B _{roof}	
Reaction to fire ^a	A2-s1,d0	
Water impermeability	No water drops	
Dimensional variations ^a	Sheets Length: ±10mm Width: +10 / -5mm Thickness: ±0.6mm Fittings Length and width: ±10mm Thickness: ±1mm	
Release of dangerous substances ^a	NPD	
Durability against		
- warm water	RL ≥ 0.7	
- soak dry	RL ≥ 0.7	
- freeze thaw	RL ≥ 0.7	
- heat rain	Pass	

^a Characteristics which apply to fittings. All characteristics apply to profiled sheets.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jayne Arkell, Country Manager.

At  on 7.8.19

.....